


## 800 STATIONARY CLEANUP IS IN THE BAG


- Ideal for all wet or dry material, from fine dust to heavy pellets or sludge
- 20 to 75HP electric motor
- Up to 1,800 CFM & 16" HG PD blower
- Convey up to 500' through Hi-Vac designed manifold systems
- Multiple hopper or continuous discharge options
- Multiple discharge height options
- Optional explosion-proof configurations
- Optional equipment protection feature



Design to Suit Manifold Systems



Easy Filter Access



Hopper or Continuous Discharge



Full Explosion-Proof Options List



## 800 STATIONARY STANDARD SPECIFICATIONS



### POWERHEAD

- TEFC electric motor, 460V/3PH/60Hz
- Horsepower ranges from 20 to 75
- Positive displacement vacuum pump capable of producing up to 1,800 CFM and 16" HG
- Spring-loaded vacuum relief valve set at 16" HG
- Equipped with vacuum pump discharge silencer

### FILTRATION

- Two-stage system with primary radial flow inlet and up to 99% efficient GORTEX dust collection filter cartridges
- Wide-pleat filter cartridge design
- Automatically handles both "Wet" and "dry" material
- Continuous reverse air-pulse filter cartridge cleaning system
- Filter cartridge top access through assisted lift and swing-out lid assembly and side-door access
- Automatic dirty filter unit shutoff

### HOPPER

- 0.5 to 2.0 cubic yard hoppers
- Automatic full hopper unit shutoff
- Several available discharge heights
- Multiple material discharge gate options

### CONSTRUCTION

- 3/16" steel plate baghouse, powerhead skid, and hopper
- Round dust collector design
- Gasketed dished head lid
- Abrasion resistant primary radial flow inlet

### CONTROLS

- NEMA 4 control panel enclosure
- Circuit breaker with manual disconnect
- 120V control circuit
- Magnetic starter with thermal overloads
- Vacuum gauge calibrated in inches & centimeters of HG
- Differential gauge
- Air pressure gauge
- Time totalizer with total hours of operation
- Auto/manual selector switch for filter cleaning
- E-Stop button

### MANIFOLD SYSTEMS

- Conveying distances up to 500'
- Full consultive design services available
- Standard CAD drawings with detailed bills of materials provided for all projects
- Comprehensive project management services, including initial and pre-installation walkthroughs, provided for all projects

### OPTIONS & ACCESSORIES

- Auto slide, double-dump, and rotary airlock gates
- Flameless explosion relief vent assembly
- Dual agent Cease Fire suppression system with high purity compressed dry nitrogen
- Explosion isolation inlet valve assembly
- Stainless steel material inlet assembly
- Grounded filter cartridges
- NEMA 7/9 Control Panel for Class I & II environments
- Explosion proof electric motor
- Grounding reel assembly
- HEPA filtration
- Noise attenuation packages with maintenance access doors
- High blower discharge temperature safety shutdown
- Broken filter bag detector safety shutdown
- Allen Bradley PLC controller for remote monitoring
- Alternate voltage ranges
- On-board air compressor package
- High temp/high vac vacuum breaker assembly